



## HEATIT QUICKMAT STICKY DECOUPLING MAT 10M2

Sticky Decoupling Mat for heating cable 6mm

<b>Art.no</b>	1011229
<b>GTIN</b>	7071236020066

Heatit QuickMat Self-Adhesive is a self-adhesive polypropylene mat with rounded, square studs. The mat has pre-formed grooves for easy and precise installation of Heatit 3.5 mm heating cable, ensuring a fast and efficient installation.

The flexible cable placement contributes to even heat distribution across the entire floor surface. The underside is coated with self-adhesive glue, making the mat easy to attach to a clean, dry and stable substrate.

Heatit QuickMat Self-Adhesive is supplied on a roll and covers 10 m<sup>2</sup>. The roll size is 1 x 10 metres and the installation height is 6 mm.

The mat is used together with tile adhesive and self-levelling compound, and is well suited for installations where a fast, stable and flexible solution for electric underfloor heating is required.

The product is well suited for use with Heatit heating cables:

- Heatit GVK 6 W/m
- Heatit BVK 10 W/m
- Heatit RVK 13 W/m

Note: After installation, the mat must not be exposed to added moisture before further covering, as this may reduce the adhesive bond to the substrate.

### PRODUCT FEATURES

- Supplied on a roll: 10 m<sup>2</sup>.
- Roll size: 1 x 10 metres.
- Self-adhesive mat for fast and easy installation.
- Can be used on concrete, self-levelling compound, chipboard, wooden floors and existing tiled surfaces.
- Can replace floor gypsum board/masterboard in relevant installations.
- Pre-formed grooves adapted for 3.5 mm heating cable.
- Ensures correct and even cable spacing.
- Protects the floor against cracking caused by movements in the substrate.
- Self-adhesive underside for easy positioning and attachment to the substrate.
- Must not be exposed to added moisture after installation before further covering.
- Installation height: 6 mm.

### PRODUCT COVER

Carpet floor, Cork , Flooring, Laminate floors, Parquet floors, Slate, Tiles, Vinyl

Heatit QuickMat must be covered with suitable tile adhesive or self-levelling compound. The mat and heating cable must be fully embedded in the covering to ensure good heat transfer, a stable floor construction and protection of the cable., , When installing under tiles or natural stone, a suitable flexible tile adhesive must be used. When installing under other approved floor coverings, the mat should be covered with a suitable self-levelling compound before the final floor covering is installed., , Important: The covering thickness and type of compound must be adapted to the substrate, selected heating cable, final floor covering and the supplier's instructions. For the self-adhesive model, the mat must not be exposed to added moisture after installation before further covering, as this may affect the adhesive bond.

### PRODUCT DATA

Material	Polypropylene (PP)
Colour	Red
Covering	Parquet floors Tiles Slate Flooring Cork Carpet floor Laminate floors Vinyl

### ADDITIONAL INFO

Warranty international	2 years
------------------------	---------

### HEATING CABLE SUBSTRATE DATA

Boards per carton (pcs)	1
Sheet Thickness	6mm
Covered area per package (m <sup>2</sup> )	10m <sup>2</sup>

**PRODUCT DIMENSIONS**

Product height/diameter	6mm	Product Width	1000mm
Product length	100000mm	Product net weight	10000g

**MAINTENANCE**

No maintenance.

**RETURN AND RECYCLING**

Must be delivered as plastic waste to an approved waste reception or recycling station.  
Normally sorted as rigid plastic / plastic from building materials.  
Must not be disposed of as residual (general) waste.

**DISCLAIMER**

After installation, Heatit QuickMat must not be exposed to added moisture, as this may cause the adhesive on the underside to detach from the substrate.