Art.no	8811490
GTIN	7071236011989

Used for splicing heating cable
Material: Polyisobutylen.
Density: 1.2 ± 0.1 g/cm3

Self-flowing sealant for assembly, filling and sealing of cables. Also used as insulation between different communication connections. Very good adhesion on most dry and dust-free surfaces.

ADDITIONAL INFO

PRODUCT DIMENSIONS

Product length	230mm	Product width	170mm
Product height-/depth	40mm		

ADDITIONAL INFORMATION

Heatit Controls AB declares that this product is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).
All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.

Heatit Controls AS
Mattisrudsvingen 19, 2827 Hunndalen, Norway
Tel: +47 61 18 77 77 | post@heatit.com
heatit.com | **documents.heatit.com**